SKIN & PONTOON INTERNAL FLOATING ROOF INPUT DATA SHEET				Move to a	higher standard™	
TANK INFORMATION REQUIRED						
Tank Owner: Location:			Date:			
Tank Number: Tank Ø:			ft Tank Height: ft			
Product Stored:			Stored Product Temperature: °F			
Design S.G.:	Inlet Flow Rat	te:	Bbl/hr	Bbl/hr Inlet Nozzle Dia.: in		
Outlet Flow Rate:	Bbl/hr Tar	nk Shell Desig	gn:			
Center Column Diame 1 st Ring Roof Column Diame 2 nd Ring Roof Column Diame 3 rd Ring Roof Column Diame	ter: in ter: in	Radius: Radius: Radius:		in in in	Distance Between Poles	
Gauge Pole Diame Gauge Pole Diame Gauge Pole Diame Gauge Pole Diame	eter: in eter: in	Radius: Radius: Radius: Radius:		in in in in	in in in in	
PLEASE SELECT SEAL TYPE Primary Seal Type: Primary Fabric Material: Secondary Seal Type: Secondary Seal Material: Secondary Seal Material: Secondary Seal Material: Wiper Seal Type: Wiper Material:			F V T F	TANK ACCESSORIES / INFO. Radar Gauging Vertical Ladder Fitted (roof-to-roof) Tank Roundness / Tilt Report Floating Suction Line		
PLEASE SELECT FOAM DAM TYPE				N2 Blanketed REQUIRED IFR APPURTENANCE(S)		
Foam Dam Options:				Suspended IFR		
ADDITIONAL SEAL OPTIONS Wax Scraper Fabric Supports				Dip Funnel Rim Vent Airscoops Pigging Ve		
Shoe Shunts				Float Well	Pigging Vent Manways(s)	
COMMENTS						
	*PLEASE P		AN OF TAN	JK NOZZLES &	INTERNAL PIPING	